

Product information

MS4128-L3P

Industrial Ethernet:Archive - Industrial Ethernet:Modular Industrial Switches:Modular switches:Modular switches:Layer 3 switches:MS4128-L3P

<http://dev-catalog.beldensolutions.com/link/57078-24455-49814-49860-49862-49862-94675-87163/en/conf/uistate>

Name		MS4128-L3P
		
		Power MICE, modular, managed Industrial Ethernet Switch, Layer 3 Switch with Software Professional. Ethernet (10 Mbit/s) and Fast-ETHERNET (100 Mbit/s) and Gigabit-Ethernet (1000 Mbit/s)
Delivery informations		
Availability		no longer available
Product description		
Description		Power MICE, modular, managed Industrial Ethernet Switch, Layer 3 Switch with Software Professional. Ethernet (10 Mbit/s) and Fast-ETHERNET (100 Mbit/s) and Gigabit-Ethernet (1000 Mbit/s)
Port type and quantity		up to 28 ports above media modules practicable, 4 X 1000 BASE-SX with SFP modules or 4 x 10/100/1000 BASE-TX and 24 Fast-ETHERNET (100 Mbit/s) ports (with MB-2T)
Type		MS4128-L3P
Order No.		943 009-302
More interfaces		
Power supply/signaling contact		2 plug-in terminal blocks, 4-pin
V.24 interface		1 x RJ11 socket
USB interface		1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network size - cascability		
Line - / star topology		any
Ring structure (HIPER-Ring) quantity switches		50 (reconfiguration time < 50 ms typ. at LWL)
Power requirements		
Operating voltage		24 V DC (-25% to +30%)
Current consumption at 24 V DC		630 mA (without media modules)
Power consumption		15 W (without media modules)
Software		
Management		serial interface, web interface, SNMP V1/V2/V3, HiVision, file transfer SW HTTP/TFTP
Diagnostics		LEDs, signal contacts (24V DC / 1 A), syslog, logfile, RMON, port mirroring, Topology Discovery IEEE 802.1AB (LLDP)
Configuration		command line interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HiDiscovery, auto-configuration adapter (ACA21-USB)
Security		authentication 802.1x, port-security IP and MAC, SNMP V3, ACL (L2/L3/L4 packet filtering) 100 / port
Other services		QoS 8 classes, port prioritisation IEEE 802.1D/p, VLAN IEEE 802.1Q, Multicast (IGMP Snooping/Querier), GMRP, Broadcast- UC-, MC-Limiter, Fast Aging, Flow Control IEEE 802.3x, PTP client (Precision Time Protocol, IEEE 1588), SNTP (Simple Network Time Protocol), Traffic Shaping, protocol based VLANs, static routing, dynamic routing RIP V1/2, OSPF, VRRP, multicast routing PIM-DM, DVMRP, IGMP V1/V2/V3
Redundancy		
Redundancy functions		HIPER-Ring (ring structure), RSTP IEEE 802.1w (rapid spanning tree protocol), redundant network/ring coupling (master/receiver functionality), dual homing (master/receiver functionality), redundant 24 V power supply
Ambient conditions		
Operating temperature		0 °C ... 60 °C
Storage/transport temperature		-40 °C ... 70 °C
Relative humidity (non-condensing)		10 % ... 95 %
MTBF		24.2 years; MIL-HDBK 217F: Gb 25 °C
Mechanical construction		
Dimensions (W x H x D)		315 mm x 134 mm x 140 mm
Mounting		DIN Rail
Weight		2200 g
Protection class		IP20
Mechanical stability		
IEC 60068-2-27 shock		15 g, 11 ms duration, 18 shocks

Industrial Ethernet:Archive - Industrial Ethernet:Modular Industrial Switches:Modular switches:Modular switches:Layer 3 switches:MS4128-L3P
<http://dev-catalog.beldensolutions.com/link/57078-24455-49814-49860-49862-49862-94675-87163/en/conf/ui/state>

IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd
Railway norm	EN50121-4
Scope of delivery and accessories	
Scope of delivery	device, 2 terminal blocks, operating manual
Accessories to order separately	rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, terminal cable, HiVision network management, auto-configuration adapter (ACA21-USB), 19" installation frame, labels ML-MS2/MM, additional backplane MB-2T

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.