



Tipo : Type :		D10/C		do: 10 mm
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range
CE - UKCA		60	0,77; >3 bar 0,86	0,3 - 60,0 bar
EAC		60	0,77; >3 bar 0,86	0,3 - 60,0 bar
ATEX Ex h II 2 Gb - UKEX		60	0,77; >3 bar 0,86	0,3 - 60,0 bar
ATEX Ex h II 2 Db - UKEX		60	0,77; >3 bar 0,86	0,3 - 60,0 bar
ASME XIII - CRN (Canada)		60	0,629	1,0 - 60,0 bar
SELO - TSG		60	0,629	1,0 - 60,0 bar
CONFIGURAZIONE - CONFIGURATION				
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel	
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut	Con ghiera With ring nut	
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	
	/	/	/	
	/	/	/	
	/	/	/	
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C	N.B.R. (Std) -10 / + 100 °C	N.B.R. (Std) -10 / + 100 °C	
	E.P.D.M. -50 / + 150 °C	E.P.D.M. -50 / + 150 °C	E.P.D.M. -50 / + 150 °C	
	VITON -20 / +200 °C	VITON -20 / +200 °C	VITON -20 / +200 °C	
	SILICONE -60 / +200 °C	SILICONE -60 / +200 °C	SILICONE -60 / +200 °C	
	PTFE -196 / +250 °C	PTFE -196 / +250 °C	PTFE -196 / +250 °C	
Connessione Entrata Inlet Connection	KALREZ -20 / +250 °C	KALREZ -20 / +250 °C	KALREZ -20 / +275 °C	
	/	Metal -196 / +250 °C	Metal -196 / +450 °C	
	G.3/8" - 1/2" ISO228	G.3/8" - 1/2" ISO228	G.3/8" - 1/2" ISO228	
	G.1/2" ISO228 F.	G.1/2" ISO228 F.	G.1/2" ISO228 F.	
	R.3/8" - 1/2" EN10226	R.3/8" - 1/2" EN10226	R.3/8" - 1/2" EN10226	
Connessione Uscita Outlet Connection	3/8" - 1/2" NPT	3/8" - 1/2" NPT	3/8" - 1/2" NPT	
	DN15 PN16-40	3/4" Tri Clamp	3/4" Tri Clamp	
	1/2" 150-300 lb	DN15 PN16-40-60	DN15 PN16-40-60	
	/	1/2" 150-300 lb	1/2" 150-300 lb	
	/	/	/	
	/	/	/	
	/	/	/	
	/	/	/	
	/	/	/	
	/	/	/	

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register.
 On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note:

Nuova General Instruments Loc. Campasso 29010 Pianello V.T. - PC - ITALY

Ed. 2022